

产品技术规范 DATA SHEET V1.0

Low Loss and Phase Stable Flexible Coaxial Cable Series

产品规格 Product Type		STC-190		
结构图 Structure Drawing				
结构特性 Structure Characteristics				
结构 Structure	项目 Item	标准值 Standard Value		
内导体 Inner Conductor	材质 Material	镀银铜线 Silverplated Copper Wire		
	结构 Construction(mm)	1/1.30		
	标称外径 Nom.Dia(mm)	1.30±0.02		
绝缘层 Insulation	材质 Material	低密度聚四氟乙烯 LD-PTFE		
	标称外径 Nom.Dia(mm)	3.84±0.05		
外导体 Outer Conductor	材质 Material	镀银扁铜线 Silverplated Copper Strip		
	标称外径 Nom.Dia(mm)	4.10±0.05		
	材质 Material	聚酰亚胺铝箔 PI-Al composite Tape		
	标称外径 Nom.Dia(mm)	4.30±0.05		
	材质 Material	镀银铜线 Silverplated Copper Wire		
标称外径 Nom.Dia(mm)	4.80±0.1			
护套 Jacket	材质 Material	聚全氟乙丙烯 FEP		
	标称外径 Nom.Dia(mm)	5.20±0.10		
电气性能 Electrical Characteristics				
项目 Item	标准值 Standard Value	项目 Item	频率 Frequency	标准值 Standard Value
阻抗 Impedanc (Ω)	50±2	衰减 Attenuation@20℃ (dB/m)	0.5GHz	0.18
电容 Capacitance(pF/m)	88		2.0GHz	0.37
速率 Velocity(%)	77		12.0GHz	0.98
最大工作电压 Max.Operating Voltage(V)	2000		18.0GHz	1.24
最大工作频率 Max.Operating Frequency(GHz)	28		26.0GHz	1.54
相位的机械稳定性 Phase Change VS Bending(°/GHz)	±0.6		40.0GHz	-
相位随温度变化 Phase Change VS Temperature (PPM@-40~+100℃)	≤1300			
可靠性 Dependability				
最小弯曲半径(单次)Min.Bending Radius/Single	mm	30		
最小弯曲半径(重复) Min.Bending Radius/Repeated	mm	75		
工作温度范围 Operating Temperature	℃	-55-+200		
使用提示 Trips for Use				
存储环境 Storage Environment	温度: 30℃以下, 湿度: 20-65%			
同类产品替换 Similar Cable to Replace				
微波通电缆型号 WBT Cable Type	可替代型号 Replaceable Type			
STC-190	HP190S,SFT-205,SF-104,,32055			

